



Technical Bulletin

PHENOMENAL BRANDS, Phenoseal Products
A division of DAP Products Inc.
2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-779-3265

Revised: 7/27/10

Phenoseal[®] Laminate Repair Filler

- A color-blended filler for laminate countertops
- Fills chips, scratches, cuts, and seams in most brands of laminate countertops
- Easy water clean-up

Packaging: 1.7 fl. oz. (50 mL) squeeze tube
Colors: Light Almond, Dark Gray, Khaki
UPC Numbers: 51136 24124, 51136 24122, 51136 24120

Company Identification:

Manufacturer: PHENOMENAL BRANDS, Phenoseal Products, A division of DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: Call 1-888-327-8477 or visit phenoseal.com

Order Information: 410-779-3265

Product Description:

Phenoseal[®] Laminate Countertop Repair Filler is a premium acrylic-based color-blended filler for laminate countertops. It fills chips, scratches, cuts, and seams in most brands of laminate countertops. They are slightly abrasive formulas designed to blend well with laminate countertop surfaces. They are packaged in one-time use squeeze tubes. It provides a durable waterproof seal and the cured product is mold and mildew resistant.

Suggested Uses:

For sealing laminate:

- Chips
- Scratches
- Cuts
- Seams

Adheres To:

- Laminate countertops
- Backsplashes

Surface Preparation & Application:

1. Surface must be clean and dry.
2. Remove cap and cut nozzle at 45° angle to desired bead size.
3. Fill chip/scratch/seam with product.
4. For a neat finish, smooth the bead of caulk with a finishing tool.

5. Clean up excess with damp sponge before it skins over. Cured caulk must be cut or scraped away.
6. Allow caulk to dry for at least 12 hours, depending on temperature and humidity, before exposing to water or moisture.
7. Store away from extreme heat or cold.

For Best Results:

- *Use in temperatures above 40°F.*
- *Cold temperatures and high humidity will slow down cure time.*
- *Store away from extreme heat or cold.*

Physical & Chemical Characteristics:

Tooling Time:	10 minutes
Tack Free Time:	30 minutes
Odor:	Very mild
Vehicle:	Acrylic latex polymer
Volatile:	Water
Filler:	Calcium Carbonate
Flashpoint:	None
Solids:	81% ± 2%
Weight per Gallon:	13.8 ± .02 lbs./gal.
Temperature Service Range:	-20°F to 180°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 cycles
Shelf Life:	12 months
Coverage:	9 linear ft. at a 3/16" bead size
MSDS No:	00010061006

Clean Up:

Clean up excess uncured product with a damp sponge before it skins over. Wash hands with warm water and soap. Dried material must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.phenoseal.com or by calling 410-779-3265.

Satisfaction Guaranteed:

If product fails to perform, when used as directed within one year of purchase, return used container and sales receipt to PHENOMENAL BRANDS, Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. PHENOMENAL BRANDS will not be liable for incidental or consequential damages.